

FORMULA CLASSIC 15W40

PRODUCT DESCRIPTION AND USE

FORMULA CLASSIC 15W40 High-performance engine oil for heavy-duty diesel engines, produced from highly refined mineral base oils in combination with a balanced system of additives. It provides excellent lubrication of modern turbocharged and nonturbocharged diesel engines, older engines, as well as engines of various off-road

FEATURES AND BENEFITS

- Protects engine parts from wear and tear when starting due to excellent low-temperature characteristics.
- Advanced additive system keeps engine parts clean and prolongs their service life.
- High temperature resistance and minimization of deposit formation.
- Provides excellent engine protection in high mileage vehicles.

MEETS THE SPECIFICATION AND APPROVALS:

API CH-4/CG-4/CF-4/ CF/SJ/SL, ACEA E7-04, MB 228.3, Volvo VDS-3, MAN 3275, MTU Type II, Renault Trucks RLD-2, Mack EO-N / EO-M PLUS, Cummins CES 20077 / 76, Detroit Diesel 93K215, Caterpillar ECF-1-a

TYPICAL PROPERTIES

TEST	UNIT	METHOD	VALUE UNIT
Density, 15 °C	g/cm ³	ASTM 4052	0,88
K. viscosity, 100°C	mm ² /s	ASTM D 445	14,7
Viscosity Index		ASTM D 2270	130
Flash Point	°C	ASTM D 92	240
Pour Point	°C	ASTM D 97	-30

* The above values may slightly vary depending on the production



FORMULA CLASSIC 15W40

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers.

Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies. For more information, please refer to the 'Material Safety Data Sheet'.

STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Lubrico Petrokimya A.Ş. may not be held responsible for damages and loss due to use of product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

TYPES OF PACKIN



20L, 200L



EURO MIX OIL SL.
Mercamadrid,
Zona comercial, Local C-D 4-28053 Madrid/Spain
www.euromixoil.com

