

OLGER HYDRAULIC HVLP SERIES

PRODUCT DESCRIPTION AND USE

OLGER HYDRAULIC HVLP SERIES Premium-class hydraulic oils with high viscosity index, made of high-quality paraffinic base oils and specially selected additives with high stability. Effectively prevents wear, oxidation and corrosion. Recommended for all industrial and mobile hydraulic systems, including marine equipment. Special industrial applications include construction equipment, presses, moving parts of structures, plastic molding machines. off-road equipment operating in harsh conditions.

FEATURES AND BENEFITS

- Excellent oxidative and thermal stability, reducing deposit formation.
- Extended oil life due to high chemical stability.
- Excellent wear protection, which reduces maintenance work and increases pump life.
- Perfectly protects the hydraulic system against corrosion in highly corrosive environments such as offshore.
- Separates water quickly due to their excellent demulsifying properties.
- Good low temperature fluidity for low temperature operation and stable viscosity for high loads.

MEETS THE SPECIFICATION AND APPROVALS:

DIN 51524 Part 2 (HLP), Part 3 (HVLP), Denison HF-0, HF-1, HF-2, Cincinnati Milacron P68, P69, P70, Vickers HP Vane Pump Test, M-2950 S, I-286 S

TYPICAL PROPERTIES

TEST	UNIT	METHOD	HVLP 32	HVLP 46	HVLP 68
Density, 15 °C	g/cm ³	ASTM 4052	0,872	0,879	0,885
K. viscosity, 40°C	mm ² /s	ASTM D 445	32	46	68
Viscosity Index		ASTM D 2270	170	172	174
Flash Point	°C	ASTM D 92	205	215	215
Pour Point	°C	ASTM D 97	-37	-30	-30

* The above values may slightly vary depending on the production



OLGER HYDRAULIC HVLP SERIES

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers.

Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies. For more information, please refer to the 'Material Safety Data Sheet'.

STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Lubrico Petrokimya A.Ş. may not be held responsible for damages and loss due to use of product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

TYPES OF PACKIN



20L, 200L



EURO MIX OIL SL.
Mercamadrid,
Zona comercial, Local C-D 4-28053 Madrid/Spain
www.euromixoil.com

