

OLGER PREMIUM 10W40 DPF

PRODUCT DESCRIPTION AND USE

OLGER PREMIUM 10W40 DPF high-quality fully synthetic engine oil with a long service life to provide effective protection for the next generation of heavy-duty diesel engines. Created using the latest low ash additive packages to maintain engine

FEATURES AND BENEFITS

- Advanced additive technology provides excellent engine wear protection under extreme operating conditions to help extend engine life.
- Superior thermal and oxidative stability is maintained over extended oil change intervals as recommended by engine manufacturers.
- High-performance detergent additives keep engine parts clean and reduce maintenance costs.

MEETS THE SPECIFICATION AND APPROVALS:

API CI-4 plus, ACEA E6/E7-12, MB-228.51/226.9, MAN M3477/M3271-1, Volvo VDS-3, Renault Trucks RLD-2/RXD/RGD, MTU Type 3.1, Deutz DQC-III-10 LA, Cummins CES 20076/77, Mack EO-N, JASO DH-2

TYPICAL PROPERTIES

TEST	UNIT	METHOD	VALUE UNIT
Density, 15 °C	g/cm ³	ASTM 4052	0,878
K. viscosity, 100°C	mm ² /s	ASTM D 445	15,83
Viscosity Index		ASTM D 2270	150
Flash Point	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-35

* The above values may slightly vary depending on the production



OLGER PREMIUM 10W40 DPF

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers.

Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies. For more information, please refer to the 'Material Safety Data Sheet'.

STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Lubrico Petrokimya A.Ş. may not be held responsible for damages and loss due to use of product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

TYPES OF PACKIN



20L, 200L



EURO MIX OIL SL.
Mercamadrid,
Zona comercial, Local C-D 4-28053 Madrid/Spain
www.euromixoil.com

