

## QUANT M 10W40

### PRODUCT DESCRIPTION AND USE

**QUANT M 10W40** is synthetic-based engine oil developed for gasoline and diesel engines of passenger cars. It provides excellent engine protection due to the advanced formula using high quality base oils and the latest additive technology.

### FEATURES AND BENEFITS

- Protects the engine from abrasive wear, providing fast lubrication of engine parts due to excellent fluidity in cold weather conditions.
- Minimizes oil loss due to specially selected base oils.
- Active cleaning ability controls deposit formation and keeps the engine clean.
- Perfectly protects the engine in all climatic and road conditions due to its high performance characteristics.

### MEETS THE SPECIFICATION AND APPROVALS:

API SL/CF, ACEA A3/B4, MB 229.1, VW 501.00/505.00, RN710, Fiat 9.55535-D2

### TYPICAL PROPERTIES

| TEST                | UNIT               | METHOD      | VALUE UNIT |
|---------------------|--------------------|-------------|------------|
| Density, 15 °C      | g/cm <sup>3</sup>  | ASTM 4052   | 0,87       |
| K. viscosity, 100°C | mm <sup>2</sup> /s | ASTM D 445  | 15,75      |
| Viscosity Index     |                    | ASTM D 2270 | 145        |
| Flash Point         | °C                 | ASTM D 92   | 230        |
| Pour Point          | °C                 | ASTM D 97   | -32        |

\* The above values may slightly vary depending on the production



## QUANT M 10W40

### HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers.

Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies. For more information, please refer to the 'Material Safety Data Sheet'.

### STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Lubrico Petrokimya A.Ş. may not be held responsible for damages and loss due to use of product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

### TYPES OF PACKIN



1L, 4L, 60L, 200L



EURO MIX OIL SL.  
Mercamadrid,  
Zona comercial, Local C-D 4-28053 Madrid/Spain  
[www.euromixoil.com](http://www.euromixoil.com)

