

QUANT M ULTRA FD 5W30

PRODUCT DESCRIPTION AND USE

RINNOL QUANT M ULTRA FD 5W30 — synthetic engine oil that provides extended engine performance, increased engine protection and additional fuel economy. Specially formulated to meet primarily Ford requirements, but also suitable for use in other brands of vehicles with the appropriate requirements.

FEATURES AND BENEFITS

- Provides fuel economy and maximizes engine performance by reducing friction
- Demonstrates a high level of thermal stability and excellent protection against oxidation
- Maintains the highest level of protection against the formation of all types of scale
- Protects the engine from wear and tear by providing fast lubrication of engine parts during start-up due to excellent fluidity in cold weather conditions
- Reduces oil consumption due to low volatility, which helps to reduce hydrocarbon content in exhaust gases

MEETS THE SPECIFICATION AND APPROVALS:

API SL/CF, ACEA A5/B5, Ford WSS-M2C913-D, Ford WSS-M2C913-C, Jaguar Land Rover STJLR.03.5003

TYPICAL PROPERTIES

TEST	UNIT	METHOD	VALUES
Density, 15 °C	mm ² /s	ASTM 4052	0,85
K. viscosity, 100°C	mm ² /s	ASTM D 445	11,9
Viscosity Index		ASTM D 2270	250
Flash Point	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-33

* The above values may slightly vary depending on the production



QUANT M ULTRA FD 5W30

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers.

Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies. For more information, please refer to the 'Material Safety Data Sheet'.

STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Lubrico Petrokimya A.Ş. may not be held responsible for damages and loss due to use of product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

TYPES OF PACKIN



1L, 4L, 60L, 200L



EURO MIX OIL SL.
Mercamadrid,
Zona comercial, Local C-D 4-28053 Madrid/Spain
www.euromixoil.com

