

SELENIUM AGRI 15W-40

PRODUCT DESCRIPTION AND USE

RINNOL SELENIUM AGRI 15W-40 is a premium all-season engine oil for the diesel engines of the latest generations of tractors and other agricultural equipment. Developed for engines operating under heavy loads at low or high speeds. Provides outstanding lubrication characteristics and excellent protection for turbocharged and non-turbocharged diesel engines.

FEATURES AND BENEFITS

- Thanks to its excellent thermal stability it provides reliable lubrication of engine parts under difficult and long operating conditions, even in summertime.
- Excellent resistance to oxidation ensures excellent lubrication throughout the life of the oil.

MEETS THE SPECIFICATION AND APPROVALS:

API CI-4/SL, ACEA E7-12, JASO DH-1, MB 228.3, MAN 3275-1, MTU, DDC Type 2, Volvo VDS-3, Renault Trucks RLD-2, MACK EO-N/EO-M+, CUMMINS CES 20076/78, Detroit Diesel DDC 93K215, Allison C4 Level

TYPICAL PROPERTIES

TEST	UNIT	METHOD	VALUE UNIT
Density, 15 °C	g/cm ³	ASTM 4052	0,884
K. viscosity, 100°C	mm ² /s	ASTM D 445	14,4
Viscosity Index		ASTM D 2270	135
Flash Point	°C	ASTM D 92	240
Pour Point	°C	ASTM D 97	-28

* The above values may slightly vary depending on the production



SELENIUM AGRI 15W-40

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers.

Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies. For more information, please refer to the 'Material Safety Data Sheet'.

STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Lubrico Petrokimya A.Ş. may not be held responsible for damages and loss due to use of product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

TYPES OF PACKIN



20L, 200L



EURO MIX OIL SL.
Mercamadrid,
Zona comercial, Local C-D 4-28053 Madrid/Spain
www.euromixoil.com

