

## SELENIUM AGRI T422 10W30

### PRODUCT DESCRIPTION AND USE

**SELENIUM AGRI T422 10W30** is multi-purpose gear oil (UTTO) for automatic and mechanical transmissions, hydraulic, axle, wet brake systems, on-board gears and power take-off mechanisms of tractors and other agricultural machinery. High-quality base oils and modern anti-friction additives ensure high performance characteristics of power transmissions of moving mechanisms.

### FEATURES AND BENEFITS

- Excellent viscosity-temperature characteristics ensure reliable operation even at very low temperatures.
- Anti-friction additives provide high efficiency and quiet operation of the wet brake system.
- Specially formulated formula ensures long service life due to high anti-corrosion and anti-foam properties.
- Prevention of deposit formation and increased efficiency of units and assemblies due to high thermal and oxidative stability.

### MEETS THE SPECIFICATION AND APPROVALS:

API GL-4, JD J-20C, CASE MS-1209, MS-1206, MS-1207, MS-1210, FNHA-2-C-200, FNHA-2-C-201  
FORD ESN-M2C86-B, ESN-M2C86-C, ESN-M2C-134 A,B,C,D, VCE WB101, CASE NEW HOLLAND  
MAT 3525,3526, CATERPILLAR TO-2, Massey Ferguson M-1135, M-1141, M-1143, M-1145  
ALLISON C-4, ZF TE-ML 03E, TE-ML 03F, TE-ML 05F, TE-ML 06K

### TYPICAL PROPERTIES

TEST	UNIT	METHOD	VALUE UNIT
Density, 15 °C	g/cm <sup>3</sup>	ASTM 4052	0,874
K. viscosity, 100°C	mm <sup>2</sup> /s	ASTM D 445	11,54
Viscosity Index		ASTM D 2270	140
Flash Point	°C	ASTM D 92	226
Pour Point	°C	ASTM D 97	-30

\* The above values may slightly vary depending on the production



## **SELENIUM AGRI T422 10W30**

### **HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS**

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers.

Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies. For more information, please refer to the 'Material Safety Data Sheet'.

### **STORAGE CONDITIONS**

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Lubrico Petrokimya A.Ş. may not be held responsible for damages and loss due to use of product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

### **TYPES OF PACKIN**



**20L, 200L**



EURO MIX OIL SL.  
Mercamadrid,  
Zona comercial, Local C-D 4-28053 Madrid/Spain  
[www.euromixoil.com](http://www.euromixoil.com)

