

TOP GEAR 75W EP GL4

PRODUCT DESCRIPTION AND USE

TOP GEAR 75W EP GL4 this is a special energy-saving transmission oil based on synthetic base oils and high-quality additives. It is intended for use in manual transmissions of passenger cars and light commercial vehicles.

FEATURES AND BENEFITS

- Provides effective wear protection both in conditions of high speed and low torque, and in conditions of low speed and high torque.
- Excellent viscosity-temperature characteristics ensure reliable operation even at very low temperatures.
- The specially developed formula ensures a long service life due to its high anti-corrosion and anti-foam properties.
- Preventing the formation of deposits and improving the efficiency of gearboxes due to high thermal and oxidative stability.

MEETS THE SPECIFICATION AND APPROVALS:

API GL-4, for all Renault-Nissan-Mitsubishi vehicles equipped with manual transmissions Sx, Jx, Tx, NDx, Ndx 1, Pxx, DBx.

TYPICAL PROPERTIES

TEST	UNIT	METHOD	VALUE UNIT
Density, 15 °C	g/cm ³	ASTM 4052	0,85
K. Viscosity, 100°C	mm ² /s	ASTM D 445	7,0
Viscosity Index		ASTM D 2270	150
Flash Point	°C	ASTM D 92	210
Pour Point	°C	ASTM D 97	-42

* The above values may slightly vary depending on the production



TOP GEAR 75W EP GL4

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers.

Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies. For more information, please refer to the 'Material Safety Data Sheet'.

STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Lubrico Petrokimya A.Ş. may not be held responsible for damages and loss due to use of product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

TYPES OF PACKIN



1L , 20L , 200L



EURO MIX OIL SL.
Mercamadrid,
Zona comercial, Local C-D 4-28053 Madrid/Spain
www.euromixoil.com

