

## TOP GEAR 9 FE 75W90 GL4/GL5

### PRODUCT DESCRIPTION AND USE

**RINNOL TOP GEAR 9 FE 75W90 GL4/GL5** — highly efficient synthetic universal transmission oil for all mechanical transmission units from gearboxes to main gear reducers, including hypoid ones. Thanks to the use of high-quality base oils and an advanced additive package, the oil has excellent low-temperature fluidity and stability at high temperatures, providing excellent protection against wear of transmission elements in a wide range of workloads.

### FEATURES AND BENEFITS

- Combines excellent thermal stability and compatibility with gearbox synchronizers with extended service life and excellent wear protection required for high-load hypoid gears.
- Increases the efficiency of the transmission, preventing the formation of deposits due to high thermal and oxidative stability.
- Provides a long service life of mechanical gearboxes, perfectly protecting them from corrosion, rusting and foaming thanks to a specially developed formula.
- Helps to increase replacement and maintenance intervals, reducing maintenance costs.

### MEETS THE SPECIFICATION AND APPROVALS:

API GL-4, API GL-5, MIL-L 2105 D, MAN 342 M-2, ZF TE ML 05A,7A, 12E, 16B, C&D, 17B, 19B, 21A, 21B, Scania ST0 1:0, Volvo 1273.10 (97310), SAE J2360, ZF 08, ZF 12A, MAN 342 M-1

### TYPICAL PROPERTIES

TEST	UNIT	METHOD	VALUE UNIT
Density, 15 °C	g/cm <sup>3</sup>	ASTM 4052	0,86
K. Viscosity, 100°C	mm <sup>2</sup> /s	ASTM D 445	14,5
Viscosity Index		ASTM D 2270	150
Flash Point	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-42

\* The above values may slightly vary depending on the production



## TOP GEAR 8 EP 75W80 GL4

### HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers.

Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies. For more information, please refer to the 'Material Safety Data Sheet'.

### STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Lubrico Petrokimya A.Ş. may not be held responsible for damages and loss due to use of product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

### TYPES OF PACKIN



1L , 20L , 200L



EURO MIX OIL SL.  
Mercamadrid,  
Zona comercial, Local C-D 4-28053 Madrid/Spain  
[www.euromixoil.com](http://www.euromixoil.com)

