

TOP GEAR ATF DX III

PRODUCT DESCRIPTION AND USE

TOP GEAR ATF DX III is automatic transmission oil designed to meet the requirements of the DEXRON III specification. Meets the needs of modern electronically controlled automatic transmissions that operate under difficult conditions, including high operating temperatures. Suitable for use in electronic controlled automatic transmissions and hydraulic steering systems of cars and trucks, requiring oils that meet the specifications of GM Dexron III G and Ford Mercon. Also can be used for hydraulic power systems in accordance with equipment manufacturer's recommendations.

FEATURES AND BENEFITS

- Extends the service life of the automatic transmission due to the high quality anti-corrosion and antioxidant additives in its composition. operation and driving.
- Minimizes friction in a wide range of operating temperatures, distributes heat and provides perfect gear shifting.
- Recommended for use in automatic transmissions of most cars and trucks.

MEETS THE SPECIFICATION AND APPROVALS:

GM Dexron III H, Ford Mercon ve Mercon V, MAN 339 Type Z2 ve V2, Allison C4, Allison TES 295, ZF TE-ML-14B, Voith55.6336

TYPICAL PROPERTIES

TEST	UNIT	METHOD	VALUE UNIT
Density, 15 °C	g/cm ³	ASTM 4052	0,853
K. viscosity, 100°C	mm ² /s	ASTM D 445	7,75
Viscosity Index		ASTM D 2270	170
Flash Point	°C	ASTM D 92	215
Pour Point	°C	ASTM D 97	-42

* The above values may slightly vary depending on the production



TOP GEAR ATF DX III

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers.

Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies. For more information, please refer to the 'Material Safety Data Sheet'.

STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Lubrico Petrokimya A.Ş. may not be held responsible for damages and loss due to use of product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

TYPES OF PACKIN



1L, 4L, 20L



EURO MIX OIL SL.
Mercamadrid,
Zona comercial, Local C-D 4-28053 Madrid/Spain
www.euromixoil.com

