

TOP GEAR EP 75W90 GL5

PRODUCT DESCRIPTION AND USE

TOP GEAR EP 75W90 GL5 is full synthetic transmission oil specially formulated for Mercedes-Benz vehicles based on next-generation polyalphaolefin (PAO) base oils and special additive technology. Suitable for the longest oil change intervals.

FEATURES AND BENEFITS

- Provides optimum lubrication in a wide temperature range due to its high viscosity index.
- Increases transmission efficiency by preventing deposit formation due to high thermal and oxidative stability.
- Provides easy gear shifting even at low temperatures.
- Provides perfect protection against wear of bearings and gears even in the toughest operating conditions.
- Reduces power loss due to lower operating temperatures compared to conventional gear oils and provides longer oil change intervals.

MEETS THE SPECIFICATION AND APPROVALS:

API GL-5, (eqv. MIL-L-2105D), MAN 342 M-2, ZF-TE-ML 05A, 7A, 12E, 16B, C and D, 17B, 19B, 21B

TYPICAL PROPERTIES

TEST	UNIT	METHOD	VALUE UNIT
Density, 15 °C	g/cm ³	ASTM 4052	0,87
K. viscosity, 100°C	mm ² /s	ASTM D 445	13,5
Viscosity Index		ASTM D 2270	160
Flash Point	°C	ASTM D 92	220
Pour Point	°C	ASTM D 97	-42

* The above values may slightly vary depending on the production



TOP GEAR EP 75W90 GL5

HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breathe heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage, sewage and should be collected by licensed waste oil collectors. It should not be mixed with any petroleum products or chemicals. It should not be burned in furnaces and boilers.

Should be kept away from children. Empty containers should not be thrown to the garbage or left in the environment and should be delivered to licensed recycling companies. For more information, please refer to the 'Material Safety Data Sheet'.

STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not be in contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. Lubrico Petrokimya A.Ş. may not be held responsible for damages and loss due to use of product outside its normal or intended uses or due to inherent dangers of the product and its consequences.

TYPES OF PACKIN



1L, 20L



EURO MIX OIL SL.
Mercamadrid,
Zona comercial, Local C-D 4-28053 Madrid/Spain
www.euromixoil.com

