

## RINNOL SELENIUM AGRI XR 15W-40

### PRODUCT DESCRIPTION AND USE

**RINNOL SELENIUM AGRI XR 15W-40** is a high-performance engine oil formulated to be used in the engines of tractors, combine harvesters and other agricultural equipment. It is suitable for use in turbo diesel engines of tractors.

### FEATURES AND BENEFITS

- Thanks to its stable structure, it provides easy lubrication during first start-up in cold weather.
- Provides effective protection against all kinds of corrosion that may occur in the engine.
- It provides problem-free lubrication without loss even in vehicles operating under heavy load.
- The detergent and dispersant additives it contains effectively reduce the formation of carbon deposits and varnish and provide the oil with improved thermal oxidation stability.

### SPECIFICATIONS AND APPROVALS

API CF-4

### HEALTH, SAFETY AND ENVIRONMENTAL RECOMMENDATIONS

Should not make contact with the skin, should not be swallowed and vapors should not be inhaled. In case of contact with the skin or eyes, wash with plenty of water and seek medical attention if necessary. When swallowed, victim should not be vomiting and immediate medical attention should be sought. When the vapors are inhaled, breath heavily in fresh air and, if necessary, seek medical attention. Used oils should not be disposed to garbage and sewage, should be collected by licensed waste oil collectors. Should be kept away from children. Empty containers should not be thrown to the garbage or left to the receiving environment and should be delivered to licensed recycling companies.

### STORAGE CONDITIONS

Packaging should not be exposed to extended periods of direct sunlight. Packaging should not contact with water. Oils should not contact with dust and should be kept away from dusty environments. Ambient temperature should not exceed 40 ° C. The user is solely responsible for using the product according to its purpose and for complying with the laws and regulations in effect. The Company is not responsible for damage or loss caused by the misuse of the product or by inherent hazards and their consequences.

### TYPICAL VALUE

TEST	UNIT	METHOD	VALUES
Density @ 15°C	g/cm <sup>3</sup>	ASTM D 4052	0,880 – 0,895
K.Viscosity @ 100 °C	cSt	ASTM D 445	12,5 – 16,3
Viscosity Index		ASTM D 2270	Min.130
Flash Point	°C	ASTM D 92	Min.240
Pour Point	°C	ASTM D 97	Max.-24

### PACKAGING TYPES

20L  
208L

